



GroupePSV



Manufacturer



CATALOGUE 2025



Manufacturer



Our mission : quality

PSV Group has been manufacturing quality machines for the meat processing industry in the artisanal and small industry sectors for several generations.

Our market knowledge allows us to develop and refine machines that meet your requirements and keep pace with the evolution of your industries. Thus, we were among the first to market compact mincers and refrigerated that meet the stringent requirements of our industry while considering hygiene and safety standards.

TABLE OF CONTENTS

REFRIGERATED MINCERS	3-4	SAUSAGE CUTTER	15
- DRC CR82 ET DRC CR22 REFRIGERATED MINCERS	3	- CSM NEW	15
- DRC CR82 REFRIGERATED MINCERS	3	STEAK FORMER	15
- DRC CR82/22 REFRIGERATED MINCERS & MULTICALIBER NEW	3	- PLA	15
- DRC VR82 WINDOW REFRIGERATED MINCER	3	BRINE PUMP	16
- DRC R98 / R32 REFRIGERATED MINCERS	4	- PM3 BRINE PUMP	16
- DRC R98 REFRIGERATED MINCER & BURGER FORMER NEW	4	- PM4 BRINE PUMP NEW	16
- BURGER FORMER	4	PSV SLICERS	17-18
TRADITIONAL MINCERS	5-6	- PS250E BELT SLICER	17
- DRC 82 / DRC 22 TABLE TOP MINCERS	5	- PS300E BELT SLICER	17
- DRC 98 / DRC 32 TABLE TOP MINCERS	5	- PS350E BELT SLICER	17
- DRC 114 ST TABLE TOP MINCERS NEW	5	- GS 300 SA BELT SLICER NEW	17
- DRC 98S / DRC 32S STANDING MINCERS NEW	6	- PSX350/PSX350 NR PINION SLICER	18
- DRC 114 STANDING MINCERS	6	- PSX350 SA NR PINION SLICER	18
- DRC 42 / DRC 130 STANDING MINCERS	6	- PSV R300 & PSV N300 MANUAL HANDWHEEL SLICER	18
CHOPPERS AUTOMATIC MIXERS	7-8	BONE SAWS	19-20
- DRC HM 45L TABLE TOP NEW	7	- SS1600 TABLE BONE SAW	19
- DRC HM 45L FLOOR STANDING NEW	7	- SS1740 TABLE BONE SAW	19
- DRC HM 100L FLOOR STANDING NEW	8	- SS1985 TABLE BONE SAW	19
MIXERS	9-10	- SS2340 FLOOR-STANDING BONE SAW	20
- VILLA M30 30 LITRE TABLE TOP MIXER	9	- SS2500 FLOOR-STANDING BONE SAW	20
- VILLA M60 NM / M60 CM 60 LITRE FLOOR STANDING MIXERS	9	- SS3155 FLOOR-STANDING BONE SAW	20
- VILLA M100 100 LITER FLOOR STANDING MIXER	9	CHOP CUTTER	21
- VILLA M125 125 LITER FLOOR STANDING MIXER	10	- CC 650 NEW	21
- VILLA M170 170 LITER FLOOR STANDING MIXER	10	- CC 750 , CC 1050 NEW	21
BOWL CHOPPERS	11-12	REFRIGERATED COUNTER	22
- VILLA C15 TABLE TOP CHOPPER 15 LITERS	11	- VPM2000 MOBILE FOLDABLE COUNTER	22
- VILLA C30 FLOOR STANDING BOWL CHOPPER 30 LITERS	11	PLATES AND KNIVES FOR MINCERS	23
- VILLA C50 FLOOR STANDING BOWL CHOPPER 50 LITERS	11	- UNGER	23
- VILLA CT-50 FLOOR STANDING BOWL CHOPPER 50 LITERS NEW	12	- ENTERPRISE	23
HYDRAULIC FILLERS AND MANUAL	13-14	BONE SAW BLADES	24
- VILLA 13 HYDRAULIC FILLER, 13 LITERS, FLOOR STANDING	13	AMERICAN HANDSAW BLADES	24
- VILLA 25 HYDRAULIC FILLER, 25 LITERS, FLOOR STANDING	13	HANDSAW AMERICAN	24
- VILLA 40 HYDRAULIC FILLER, 40 LITERS, FLOOR STANDING	13		
- VILLA 60 HYDRAULIC FILLER, 60 LITERS, FLOOR STANDING NEW	13		
- VILLA ST13 HYDRAULIC TABLE TOP FILLER	14		
- VILLA PV13 MANUAL TABLE TOP FILLER	14		
ACCESSORIES	14		
- FRONT WHEEL VILLA 13/25/40 HYDRAULIC FILLERS	14		
- PORTIONER VILLA 13/25/40 HYDRAULIC FILLERS	14		
- KEFTA DEVICE	14		
- BURGER FORMER	14		



REFRIGERATED MINCERS



DRC CR82 and DRC CR22

Model	Size without burger former (mm)	Packaging (mm)	Weight (kg)	Capacity (kg/h)	Motor power	Frequency	Voltage
DRC CR 82 DRC CR 22	482 x 363 x 579	670 x 480 x 705	45	300	1,5 CV 1,1 kW	50/60 Hz	3/380 V

GENERAL FEATURES

- CR82 - Unger H82 (delivered with 3 mm plate)
- CR22 - Enterprise N22 (Delivered with 3 mm plate)

OPTION

- Single phase motor

Machine conforms to standards **CE**



DRC CR82 With burger former

Model	Size with burger former (mm)	Packaging (mm)	Weight (kg)	Capacity (kg/h)	Motor power	Frequency	Voltage
DRC CR 82	521 x 506 x 579	670 x 480 x 705	45	300	1,5 CV 1,1 kW	50/60 Hz	3/380 V

GENERAL FEATURES

- CR82 - Unger H82 (delivered with 3 mm plate)
- Multicalibre oval burger former from 100g to 200g (Allows you to vary the diameter of your burgers)
- or
- Monocalibre round burger former (Thickness 18 mm): Ø83 (100g); Ø90 (120g); Ø100 (150g); Ø110 (170g); Ø120 (200g)

OPTION

- Single phase motor

Machine conforms to standards **CE**



DRC CR82 and CR22 Multi With single round shape former, Variable thickness



Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity (kg/h)	Motor power	Frequency	Voltage
DRC CR 82 DRC CR 22	647 x 444 x 579	670 x 720 x 705	50	300	1,5 CV 1,1 kW	50/60 Hz	3/380 V

GENERAL FEATURES

- CR82 - Unger H82 (delivered with 3 mm plate)
- CR22 - Enterprise N22 (delivered with 3 mm plate)
- Single 100 mm diameter, from 12 to 24 mm thickness (100g to 200g)

OPTION

- Single phase motor

Machine conforms to standards **CE**



DRC VR82 With burger former

Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity (kg/h)	Motor power	Frequency	Voltage
DRC VR 82	526 x 526 x 578	900 x 720 x 705	60	300	1,5 CV 1,1 kW	50/60 Hz	3/380 V

GENERAL FEATURES

- VR82 - Unger H82 (delivered with 3 mm plate)
- lightened plexi-door
- Safety switch on plexi-door
- Multicalibre oval burger former from 100g to 200g (Allows you to vary the diameter of your burgers)

OPTION

- Single phase motor

Machine conforms to standards **CE**



REFRIGERATED MINCERS



DRC R98 and DRC R32

Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity (kg/h)	Motor power	Frequency	Voltage
DRC R98	550 x 437 x 630	900 x 720 x 705	71	600	3 CV 2,2 kW	50/60 Hz	3/380 V
DRC R32	555 x 437 x 630						

GENERAL FEATURES

- R98 - Unger B98 (delivered with 5 mm plate)
- R32 - Enterprise N32 (delivered with 5 mm plate)

OPTION

- Single phase motor

Machine conforms to standards **CE**



DRC R98 With burger former



Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity (kg/h)	Motor power	Frequency	Voltage
DRC R98 REC	580 x 506 x 630	900 x 720 x 705	71	600	3 CV 2,2 kW	50/60 Hz	3/380 V

GENERAL FEATURES

- R98 - Unger B98 (delivered with 5 mm plate)
- Multicalibre oval burger former from 100g to 200g (Allows you to vary the diameter of your burgers)
- or
- Monocalibre round burger former (Thickness 18 mm) : Ø83 (100g); Ø90 (120g); Ø100 (150g); Ø110 (170g); Ø120 (200g)

OPTION

- Single phase motor

Machine conforms to standards **CE**

BURGER FORMER

Spare former (For machines originally equipped with burger former)



- Multicalibre oval burger former from 100g to 200g (Allows you to vary the diameter of your burgers)
- Monocalibre round burger former (Thickness 18 mm) : Ø83 (100g); Ø90 (120g); Ø100 (150g); Ø110 (170g); Ø120 (200g)





TRADITIONAL MINCERS

TABLE TOP



DRC 22L

Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity (kg/h)	Motor power	Frequency	Voltage
DRC 22L	490 x 320 x 410	640 x 500 x 700	28	250	1 CV 0,75 kW	50 Hz	1/230 V

GENERAL FEATURES

- External processing parts, quick and easy disassembly
- Removable tray with motor switch
- 22L - Enterprise N22 (delivered with 3 mm plate)

Machine conforms to standards **CE**



DRC 82, DRC 22

Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity (kg/h)	Motor power	Frequency	Voltage
DRC 82	560 x 337 x 444	670 x 500 x 615	38	350	1,5 CV 1,1 kW	50/60 Hz	3/380 V
DRC 22	520 x 337 x 444						

GENERAL FEATURES

- External processing parts, quick and easy disassembly
- Removable tray with motor switch
- DRC 82 - Unger H82 (delivered with 3 mm plate)
- DRC 22 - Enterprise N22 (delivered with 3 mm plate)

OPTION

- Single phase motor for DRC 82 and DRC 22

Machine conforms to standards **CE**



DRC 98 and DRC 32

Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity (kg/h)	Motor power	Frequency	Voltage
DRC 98	670 x 425 x 505	780 x 670 x 705	58	600	3 CV 2,2 kW	50/60 Hz	3/380 V
DRC 32	620 x 425 x 505						

GENERAL FEATURES

- External processing parts, quick and easy disassembly
- Removable tray with motor switch
- DRC 98 - Unger B98 (delivered with 5 mm plate)
- DRC 32 - Enterprise N32 (delivered with 5 mm plate)

OPTIONS

- Single phase motor
- Triple cut (5 cutting elements / UNGER 5) for the DRC 98 (Delivered with a Ø5 mm and Ø8 mm plate)

Machine conforms to standards **CE**



DRC 114ST

Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity (kg/h)	Motor power	Frequency	Voltage
DRC 114ST	855 x 815 x 710	1200 x 850 x 720	86	900	4 CV 3 kW	50/60 Hz	3/400 V

GENERAL FEATURES

- External processing parts, quick and easy disassembly
- Safety cover
- DRC 114 - Unger D114 (delivered with 5 mm plate)
- Delivered with LICOSWISS knives

OPTION

- Triple cut (5 cutting elements / UNGER 5) for the DRC 114 (Delivered with a Ø5 mm and Ø8 mm plate)

Machine conforms to standards **CE**





TRADITIONAL MINCERS

STANDING



DRC 98S and DRC 32S

Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity (kg/h)	Motor power	Frequency	Voltage
DRC 98S DRC 32S	1184 x 633 x 900	1370 x 1015 x 1350	100	900	4 CV 3 kW	50/60 Hz	3/380 V

GENERAL FEATURES

- External processing parts, quick and easy disassembly
- Safety cover
- 4 wheels, 2 front ones with brakes
- DRC 98S - Unger B98 (delivered with 5 mm plate)
- DRC 32S - Enterprise N32 (delivered with 5 mm plate)
- Delivered with LICOSWISS knives

OPTION

- Triple cut (5 cutting elements / UNGER 5) for the DRC 98 (Delivered with a Ø5 mm and Ø8 mm plate)

Machine conforms to standards **CE**



DRC 114

Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity (kg/h)	Motor power	Frequency	Voltage
DRC 114	1000 x 760 x 1250	1200 x 800 x 1350	129	1400	5,5 CV 4,1 kW	50/60 Hz	3/380 V

GENERAL FEATURES

- External processing parts, quick and easy disassembly
- Safety cover
- 4 wheels, 2 front ones with brakes
- DRC 114 - Unger D114 (delivered with 5 mm plate)
- Delivered with LICOSWISS knives

OPTION

- Triple cut (5 cutting elements / UNGER 5) for the DRC 114 (Delivered with a Ø5 mm and Ø8 mm plate)

Machine conforms to standards **CE**



DRC 130 and DRC 42

Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity (kg/h)	Motor power	Frequency	Voltage
DRC 130 DRC 42	1340 x 870 x 1290	1400 x 900 x 1350	139	2000	7 CV 5,5 kW	50/60 Hz	3/380 V

GENERAL FEATURES

- External processing parts, quick and easy disassembly
- Safety cover
- 4 wheels, 2 front ones with brakes
- DRC 130 - Unger E130 (delivered with 5 mm plate)
- DRC 42 - Enterprise N42 (delivered with 5 mm plate)
- Delivered with LICOSWISS knives

OPTION

- Triple cut (5 cutting elements / UNGER 5) for the DRC 130 (Delivered with a Ø5 mm and Ø8 mm plate)

Machine conforms to standards **CE**



CHOPPERS AUTOMATIC MIXERS

TABLE TOP



DRC HM 45L ST



Model	Size (mm)	Packaging (mm)	Bowl capacity	Weight (kg)	Capacity (kg/h)	Chopping motor power	Mixing motor power	Frequency	Voltage
DRC HM 45L/98 ST	829 x 632 x 661	1200 x 800 x 800	45 L	90	600	3CV 2,2 kW	0,75 CV 0,55 kW	50/60 Hz	3/380 V
DRC HM 45L/32 ST									

GENERAL FEATURES

- Mixing paddles and removable external processing parts
- Body safety cover and bowl
- Automatic mix and mince program
- DRC HM 45L/32 - Enterprise N32 (delivered with 5 mm plate)
- DRC HM 45L/98 - Unger B98 (delivered with 5 mm plate)
- Delivered with LICOSWISS knives
- Standard Schneider Electric™ and SIEMENS components

OPTION

- Single phase motor

Machine conforms to standards **CE**

Non-contractual photos

STANDING



DRC HM 45L



Model	Size (mm)	Packaging (mm)	Bowl capacity	Weight (kg)	Capacity (kg/h)	Chopping motor power	Mixing motor power	Frequency	Voltage
DRC HM 45L/98	829 x 632 x 1208	1200 x 800 x 1500	45 L	155	600	3CV 2,2 KW	0,75 CV 0,55 kW	50/60 Hz	3/380V
DRC HM 45L/32									

GENERAL FEATURES

- Mixing paddles and removable external processing parts
- Body safety cover and bowl
- Automatic mix and mince program
- DRC HM 45L/32 - Enterprise N32 (delivered with 5 mm plate)
- DRC HM 45L/98 - Unger B98 (delivered with 5 mm plate)
- Delivered with LICOSWISS knives
- Standard Schneider Electric™ and SIEMENS components

OPTION

- Single phase motor

Machine conforms to standards **CE**





CHOPPERS AUTOMATIC MIXERS

STANDING



DRC HM 100L

Model	Size (mm)	Packaging (mm)	Bowl capacity	Weight (kg)	Capacity (kg/h)	Chopping motor power	Mixing motor power	Frequency	Voltage
DRC HM 100L/114					1400				
DRC HM 100L/98	1290 x 775 x 1440	1370 x 1015 x 1600	100 L	309	1000	5,5 CV 4 KW	1,5 CV 1,1 KW	50/60 Hz	3/380V
DRC HM 100L/32					1000				

GENERAL FEATURES


- Mixing paddles and removable external processing parts
- Body safety cover and bowl
- Automatic mix and mince program
- DRC HM 100L/32 - Enterprise N32 (delivered with 5 mm plate)
- DRC HM 100L/98 - Unger B98 (delivered with 5 mm plate)
- DRC HM 100L/114 - Unger D114 (delivered with 5 mm plate)
- Delivered with LICOSWISS knives
- Standard Schneider Electric™ and SIEMENS components

OPTIONS

- Triple cut (5 cutting elements / UNGER 5) for the DRC HM 100 L/114 (Delivered with a Ø5 mm and Ø8 mm plate)
- Triple cut (5 cutting elements / UNGER 5) for the DRC HM 100L/98 (Delivered with a Ø5 mm and Ø8 mm plate)



Machine conforms to standards **CE**



MIXERS

TABLE TOP



VILLA M30

Model	Size (mm)	Packaging (mm)	Capacity	Weight (kg)	Bowl (mm)	Arm motor power	Arm rotation (RPM)	Voltage	Frequency	Quantity of mixture (kg)
VILLA M30	470 x 663 x 650	600 x 600 x 800	32 L	55	400 x 260	0,18 kW	47	3/380 V	50/60 Hz	+/- 6-15

GENERAL FEATURE

- Removable bowl with brake

OPTIONS

- Removable arm
- Single phase motor

Machine conforms to standards 

STANDING



VILLA M60 NM and VILLA M60 CM

Model	Size (mm)	Packaging (mm)	Capacity	Weight (kg)	Bowl (mm)	Arm rotation (RPM)	Voltage	Frequency	Quantity of mixture (kg)
M60 NM	707 x 550 x 877	900 x 720 x 1250	60 L	85	500 x 300	47	3/380 V	50/60 Hz	+/- 10-35
M60 CM	707 x 550 x 877	900 x 720 x 1250	60 L	85	500 x 300	Bras 47 - Cuve 11			+/- 10-35

GENERAL FEATURES

- 2 back wheels & 2 front feet
- VILLA M60 Tiltable bowl with brake
- VILLA M60CM Motorized & tiltable bowl and both ways mixing arm

OPTIONS

- Removable arm
- Single phase motor
- 4 wheels (2 swivel with brakes and 2 fixed) to order

Machine conforms to standards 



VILLA M100

Model	Size (mm)	Packaging (mm)	Capacity	Weight (kg)	Bowl (mm)	Arm rotation (RPM)	Voltage	Frequency	Quantity of mixture (kg)
VILLA M100	794 x 630 x 949	1000 x 850 x 1250	100 L	85	600 x 360	Bras 47 - Cuve 11	3/380 V	50/60 Hz	+/- 10-55

GENERAL FEATURES

- Motorized & tiltable bowl with both ways mixing arm
- Two directions of arm rotation
- 2 back wheels & 2 front feet

OPTIONS

- Removable arm
- 4 wheels (2 swivel with brakes and 2 fixed) to order

Machine conforms to standards 



MIXERS

STANDING



VILLA M125

Model	Size (mm)	Packaging (mm)	Capacity	Weight (kg)	Bowl (mm)	Arm rotation (RPM)	Voltage	Frequency	Quantity of mixture (kg)
VILLA M125	972 x 811 x 1101	1370 x 1020 x 1470	125 L	115	720 x 350	Bras 47 - Cuve 9	3/380 V	50/60 Hz	+/- 12-70

GENERAL FEATURES

- Motorized & tiltable bowl whit both ways mixing arm
- Two directions of arm rotation
- 2 back wheels & 2 front feet

OPTIONS

- Removable arm
- 4 wheels (2 swivel with brakes and 2 fixed) to order

Machine conforms to standards **CE**



VILLA M170

Model	Size (mm)	Packaging (mm)	Capacity	Weight (kg)	Bowl (mm)	Arm rotation (RPM)	Voltage	Frequency	Quantity of mixture (kg)
VILLA M170	1046 x 846 x 1132	1370 x 1020 x 1470	170 L	220	800 x 380	Bras 47 - Cuve 9	3/380 V	50/60 Hz	+/- 15-90

GENERAL FEATURES

- Motorized & tiltable bowl whit both ways mixing arm
- Two directions of arm rotation
- 2 back wheels & 2 front feet

OPTIONS

- Removable arm
- 4 wheels (2 swivel with brakes and 2 fixed) to order

Machine conforms to standards **CE**





BOWL CHOPPERS



TABLE TOP

VILLA C15

Model	Size (mm)	Packaging (mm)	Capacity	Weight (kg)	Bowl (mm)	Motor power	Rotation (RPM)	Frequency	Voltage	Quantity of mixture (kg)
VILLA C15	827 x 588 x 607	900 x 700 x 800	15 L	120	565 x 98,5	Bowl 0,15 kW or 0,09 kW knives 2,2 kW or 1,5 kW	Bowl 12 or 24 knives 1500 or 3000	50/60 Hz	3/380 V	10 kg



GENERAL FEATURES

- 3 knives head
- 2 independant motors, 2 bowl speed and 2 knives speed

OPTION

- 6 knives head

Machine conforms to standards **CE**

STANDING

VILLA C30

Model	Size (mm)	Packaging (mm)	Capacity	Weight (kg)	Bowl (mm)	Motor power	Rotation (RPM)	Frequency	Voltage	Quantity of mixture (kg)
VILLA C30	1027 x 737 x 1144	1370 x 1015 x 1540	30 L	270	702 x 128	Bowl 0,3 kW or 0,15 kW knives 4,5 kW or 3,4 kW	Bowl 12 or 24 knives 1500 or 3000	50/60 Hz	3/380 V	22 kg



GENERAL FEATURES

- 3 knives head
- 2 independant motors, 2 bowl speed and 2 knives speed

OPTION

- 6 knives head

Machine conforms to standards **CE**

VILLA C50

Model	Size (mm)	Packaging (mm)	Capacity	Weight (kg)	Bowl (mm)	Motor power	Rotation (RPM)	Frequency	Voltage	Quantity of mixture (kg)
VILLA C50	1110 x 950 x 1180	1400 x 1200 x 1550	50 L	485	828 x 155	Bowl 0,45 kW or 0,9 kW knives 6 kW or 7,5 kW	Bowl 12 or 24 knives 1500 or 3000	50/60 Hz	3/380 V	35 kg



GENERAL FEATURES

- 6 knives head
- Compensation rings for 3-knife operation
- 2 independant motors, 2 bowl speed and 2 knives speed
- Soundproof cover

OPTION

- Thermometer

Machine conforms to standards **CE**

Non-contractual photos



BOWL CHOPPERS



STANDING




VILLA CT-50

Model	Size (mm)	Packaging (mm)	Capacity	Weight (kg)	Bowl (mm)	Motor power	Rotation (RPM)	Frequency	Voltage	Quantity of mixture (kg)
VILLA CT-50	1110 x 950 x 1180	1400 x 1200 x 1550	50 L	530	828 x 155	Bowl 1,1 kW knives 10,5 kW	Bowl 6 to 24 knives 1000 to 4000	50/60 Hz	3/400 V	35 kg

GENERAL FEATURES

- 6 knives head
- Compensation rings for 3-knife operation
- 2 independent motors, variable bowl and knife speeds
- Soundproof cover
- 7" touch control panel, IP65
- All stainless steel bodywork
- Electronic board equipped with components of high reliability



Non-contractual photos

Machine conforms to standards **CE**





HYDRAULIC FILLERS



STANDING



VILLA 13, 25, 40

Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity	Motor power	Frequency	Voltage
VILLA 13	430 x 605 x 1014	800 x 680 x 1310	87	13 L - 10 kg	0,75 CV 0,55 kW	50/60 Hz	3/380 V
VILLA 25	660 x 500 x 1148	800 x 680 x 1320	138	25 L - 20 kg	1 CV 0,75 kW	50/60 Hz	3/380 V
VILLA 40	730 x 590 x 1270	1200 x 800 x 1470	245	40 L - 35 kg	1,5 CV 1,1 kW	50/60 Hz	3/380 V

GENERAL FEATURES

- 3 stainless steel nozzles 14, 20, 32 mm
- Lid and piston made of 304 thick stainless steel
- Independant hydraulic system
- 2 fixed rear wheels & 2 front feet
- Monobloc body
- Start and stop **New**

OPTION

- Single phase motor

Machine conforms to standards **CE**



VILLA 60



Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity	Motor power	Frequency	Voltage
VILLA 60	825 x 661 x 1276	1200 x 800 x 1470	310	60 L - 55 kg	1,5 CV 1,1 kW	50/60 Hz	3/380 V

GENERAL FEATURES

- 3 stainless steel nozzles 14, 20, 32 mm
- Lid and piston made of 304 thick stainless steel
- Independant hydraulic system
- 2 fixed rear wheels & 2 front feet
- Monobloc body
- Start and stop **New**

OPTION

- Single phase motor

Machine conforms to standards **CE**



HYDRAULIC FILLERS



TABLE TOP HYDRAULIC



VILLA ST13

Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity	Motor power	Frequency	Voltage
VILLA ST13	360 x 182 x 1126	800 x 680 x 1320	55	13 L - 10/12 kg	0,75 CV 0,55 kW	50 Hz	1/230 V

GENERAL FEATURES

- 3 aluminium nozzles 14, 20, 32 mm
- Foot pedal activation
- Tilttable cylinder

OPTION

- 3 stainless steel nozzles

Machine conforms to standards

TABLE TOP MANUAL



VILLA PV13

ALL S. STEEL

Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity	Cylinder (mm)
VILLA PV13	400 x 260 x 725	410 x 320 x 740	30	13 L - 10/12 kg	190 x 465

GENERAL FEATURES

- 3 aluminium nozzles 14, 20, 32 mm
- Foot pedal activation
- Cylinder, base, column, rack, casing, and crank made of stainless steel

OPTION

- 3 stainless steel nozzles

Machine conforms to standards

ACCESSORIES FOR VILLA 13, VILLA 25, VILLA 40 & VILLA 60



FRONT WHEELS

Model	Destination
SR 13	for VILLA 13 hydraulic filler
SR 25	for VILLA 25 hydraulic filler
SR 40	for VILLA 40 hydraulic filler

Stainless and equipped with two turning & braking wheels.



PORTIONER

Model	Dosing
Portioner	20 to 500 g

GENERAL FEATURE

- 3 stainless steel nozzles

OPTION

- Doser valve



KEFTA DEVICE

For Villa 13, 25, 40 and 60 hydraulic fillers



STEAK FORMER

For Villa 13, 25, 40 and 60 hydraulic fillers



SAUSAGE CUTTER



CSM

Model	Size (mm)	Packaging (mm)	Weight (kg)
CSM	590 x 640 x 400	900 x 720 x 705	19,5

GENERAL FEATURES

- Machine for manually portioning and cutting sausages
- By changing the number of clamps, you change the length of sausages
- In position 3 clamps, you make sausages ranging from 19.5 cm to 24 cm by simply adding or removing the U supports
- In position 4 clamps, you make sausages ranging from 14.5 cm to 18 cm. In position 2 clamps and 1 clamp, you will make sandwich sausages or 'brasse' sausages...

OPTION

- 2 additional clamps for the possibility of making 10 cm sausages

Machine conforms to standards **CE**



Non-contractual photos



BURGER FORMER

PLA

Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity (Pieces/hour)	Tank capacity	Motor power	Frequency	Voltage
PLA	715 x 590 x 705	750 x 620 x 715	75	2100	32L (20kg)	0,33 kW	50 Hz	1/230 V

GENERAL FEATURES

- Automatic paper dispensing system
- Burger evacuation conveyor
- Foot pedal control
- 32L tank (± 20 kg)
- Mould for burgers Ø100

OPTIONS

- 40L tank
- Extended evacuation conveyor
- Additional single mould
- Additional double mould
- Speed controller
- Pneumatic cleaning

Machine conforms to standards **CE**





BRINE PUMP

PM3

Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity	Motor power	Pressure	Frequency	Voltage
PM3	350 x 225 x 240	500 x 300 x 350	11,5	750 L/h	0,25 Kw	2.5 bars	50 Hz	1/230 V

GENERAL FEATURES

- Stainless steel body
- Single needle pistol handle



OPTIONS

- 3 needles 4 mm only
- 5 needles 4 mm only

Machine conforms to standards **CE**

PM4




Non-contractual photos

Model	Size (mm)	Packaging (mm)	Weight (kg)	Capacity	Motor power	Pressure	Frequency	Voltage
PM4	543 x 280 x 297	550 x 300 x 350	17	1620 L/h	0,56 Kw	1.5 to 4.5 bars	60/50 Hz	3/380 V

GENERAL FEATURES

- Stainless steel body
- Single needle pistol handle
- Three-phase motor



OPTIONS

- 3 needles 4 mm only
- 5 needles 4 mm only
- Single phase motor

Machine conforms to standards **CE**





PSV SLICERS

BELT DRIVEN



PS250E

Model	Size (mm)	Packaging (mm)	Weight (kg)	Blade (mm)	Slice thickness	Cutting height (mm)	Motor power	Frequency	Voltage
PS250E	605 x 470 x 430	560 x 470 x 420	20,5 kg	250	0 - 14 mm	180 x 220 x 190	176 W	50 Hz	1/230 V

GENERAL FEATURES

- Independant sharpener

OPTION

- Teflon (tray, knife, stop, blade guard)

Machine conforms to standards **CE**



PS300E

Model	Size (mm)	Packaging (mm)	Weight (kg)	Blade (mm)	Slice thickness	Cutting height (mm)	Motor power	Frequency	Voltage
PS300E	655 x 500 x 445	660 x 550 x 500	23,5 kg	300	0 - 15 mm	210 x 240 x 215	220 W	50 Hz	1/230 V

GENERAL FEATURES

- Independant sharpener

OPTION

- Teflon (tray, knife, stop, blade guard)

Machine conforms to standards **CE**



PS350E

Model	Size (mm)	Packaging (mm)	Weight (kg)	Blade (mm)	Slice thickness	Cutting height (mm)	Motor power	Frequency	Voltage
PS350E	705 x 530 x 480	780 x 620 x 510	35 kg	350	0 - 15 mm	280 x 210 x 240	301 W	50 Hz	1/230 V

GENERAL FEATURES

- Independant sharpener

OPTION

- Teflon (tray, knife, stop, blade guard)

Machine conforms to standards **CE**



GS 300 SEMI-AUTOMATIC



Model	Size (mm)	Packaging (mm)	Weight (kg)	Blade (mm)	Slice thickness	Cutting height (mm)	Motor power	Frequency	Voltage
GS 300 SA	630 x 460 x 550	680 x 600 x 650	36 kg	300	0 - 15 mm	240 x 170 x 200	0,240 Kw	50 Hz	1/230 V

GENERAL FEATURES

- Independant sharpener

OPTION


- Teflon (tray, knife, stop, blade guard)

Machine conforms to standards **CE**



PSV SLICERS

STAINLESS STEEL GEAR DRIVEN



PSX350/PSX350 NR

Model	Size (mm)	Packaging (mm)	Weight (kg)	Blade (mm)	Slice thickness	Cutting height (mm)	Motor power	Frequency	Voltage
PSX350 PSX350 NR	720 x 580 x 500	780 x 620 x 510	52 kg	350	0 - 15 mm	310 x 260 x 250	0,26 kW	50 Hz	1/230 V

GENERAL FEATURES

- Independant sharpener
- PSX350 NR equipped with a blade extractor

OPTION

- Teflon (tray, knife, stop, blade guard)

Machine conforms to standards **CE**



PSX350 SA NR SEMI-AUTOMATIC

Model	Size (mm)	Packaging (mm)	Weight (kg)	Blade (mm)	Slice thickness	Cutting height (mm)	Motor power	Frequency	Voltage
PSX350 SA NR	720 x 580 x 500	810 x 850 x 680	63 kg	350	0 - 15 mm	310 x 260 x 250	0,26 kW	50 Hz	1/230 V

GENERAL FEATURES

- Independant sharpener
- Blade extractor
- Slice countdown

OPTION

- Teflon (tray, knife, stop, blade guard)

Machine conforms to standards **CE**

PSX350 NR / SA



NR models allow for safe blade extraction

Non-contractual photos

MANUAL MODEL WITH A HANDWHEEL



PSVR300

Model	Size (mm)	Packaging (mm)	Weight (kg)	Blade (mm)	Slice thickness	Cutting height (mm)	Carriage stroke
PSVR300	840 x 620 x 1330	1220 x 800 x 930	73 kg	300	0,3 - 5mm	190 x 235 mm	285 mm


GENERAL FEATURES

- Aluminum sharpener
- Rosette with gold trim

OPTIONS

- Base (net weight 48 kg)
- Available in black (ref PSV N300)

Machine conforms to standards **CE**



BAND SAWS

TABLE TOP



SS1600

Model	Size (mm)	Packaging (mm)	Work bench (mm)	Weight (kg)	Height (mm)	Blade (mm)	Cutting height (mm)	Motor power	Frequency	Voltage
SS1600	540 x 475 x 825	710 x 620 x 1000	530 x 385	57	180	1600 x 16	180 x 175	1 CV 0,75 kW	50/60 Hz	3/380 V

GENERAL FEATURE

- Slice thickness guide

OPTION

- Mono

Machine conforms to standards **CE**



SS1740

Model	Size (mm)	Packaging (mm)	Work bench (mm)	Weight (kg)	Height (mm)	Blade (mm)	Cutting height (mm)	Motor power	Frequency	Voltage
SS1740	630 x 540 x 940	780 x 780 x 1140	620 x 430	73	220	1740 x 16	220 x 195	1,5 CV 0,75 kW	50/60 Hz	3/380 V

GENERAL FEATURE

- Slice thickness guide

OPTIONS

- Mono
- Stand (545 x 540 x 435) mm

Machine conforms to standards **CE**



SS1985

Model	Size (mm)	Packaging (mm)	Work bench (mm)	Weight (kg)	Height (mm)	Blade (mm)	Cutting height (mm)	Motor power	Frequency	Voltage
SS1985	680 x 610 x 1050	830 x 830 x 1370	670 x 480	85	250	1985 x 16	270 x 225	1,5 CV 1,1 kW	50/60 Hz	3/380 V

GENERAL FEATURE

- Slice thickness guide

OPTIONS

- Mono
- Stand (545 x 540 x 435) mm

Machine conforms to standards **CE**

BAND SAWS

STANDING



SS2340

Model	Size (mm)	Packaging (mm)	Work bench (mm)	Weight (kg)	Height (mm)	Blade (mm)	Cutting height (mm)	Motor power	Frequency	Voltage
SS2340	680 x 660 x 1635	830 x 830 x 1800	670 x 530	97	300	2340 x 16	320 x 225	2 CV 1,5 kW	50/60 Hz	3/380 V

GENERAL FEATURES

- Slice thickness guide
- Stand (545 x 540 x 435) mm

OPTION

- Mono

Machine conforms to standards **CE**



SS2500

Model	Size (mm)	Packaging (mm)	Work bench (mm)	Weight (kg)	Height (mm)	Blade (mm)	Cutting height (mm)	Motor power	Frequency	Voltage
SS2500	790 x 745 x 1670	920 x 970 x 1830	775 x 604	210	350	2500 x 16	350 x 275	3 CV 2,2 kW	50/60 Hz	3/380 V

GENERAL FEATURES

- Slice thickness guide
- Adjustable feet

OPTION

- Sliding tray

Machine conforms to standards **CE**



SS3155

Model	Size (mm)	Packaging (mm)	Work bench (mm)	Weight (kg)	Height (mm)	Blade (mm)	Cutting height (mm)	Motor power	Frequency	Voltage
SS3155	960 x 1020 x 1840	1150 x 1250 x 2005	945 x 829	270	420	3155 x 16	420 x 375	4 CV 3 kW	50/60 Hz	3/380 V


GENERAL FEATURES

- Slice thickness guide
- Adjustable feet

OPTION

- Sliding tray

Machine conforms to standards **CE**



CHOP CUTTER

TABLE TOP

CC 650



Model	Size (mm)	Packaging (mm)	Cutting capacity (mm)	Weight (kg)	Single-blade performance slices/minute	Slice thickness (mm)	Motor power	Frequency	Voltage
CC 650	1620 x 690 x 700	—	650 x 180 x 170	200	180	1 — 32	2.7 kW	50/60 Hz	3/380 V

GENERAL FEATURES

- Up to 180 slices/minute
- Shorter cycles thanks to automatic return limiter
- Smooth or serrated blade available depending on use

OPTION

- Mobile table with storage compartment



Machine conforms to standards **CE**

STANDING

CC 750, CC 1050



Model	Size (mm)	Packaging (mm)	Cutting capacity (mm)	Weight (kg)	Single-blade performance slices/minute	High-performance double blade slices/minute	Slice thickness (mm)	Motor power	Frequency	Voltage
CC 750	1860 x 800 x 1230	1300 x 1100 x 1800	750 x 210 x 230	280	220	440	1 — 32	2.7 kW	50/60 Hz	3/380 V
CC 1050	2400 x 800 x 1230		1050 x 210 x 230	320	220	440	1 — 32	2.7 kW	50/60 Hz	3/380 V

GENERAL FEATURES

- Up to 440 slices/minute
- Shorter cycles thanks to automatic return limiter
- Mobile support
- Smooth or serrated blade available depending on use



Machine conforms to standards **CE**





REFRIGERATED COUNTER

VPM2000 MOBILE FOLDABLE COUNTER

Model	Size (mm)	Packaging (mm)	Weight (kg)	Depth (mm)	Motor power	Frequency	Voltage
VPM2000	Open : 1900 x 1067 x 1240 Closed : 1900 x 440 x 1240	1960 x 440 x 1120	170	850	1,5 CV / HP 1,1 kW	50 Hz	1/230 V

GENERAL FEATURES

- Red and white striped tarpaulin
- 2 electrical sockets
- Thermometer
- Rear closures in plexiglass with vertical and independent opening for stock isolation

OPTIONS

- White LED lighting
- Coupling junction for two display cases

Machine conforms to standards **CE**



Non-contractual photos





SUPINOX RANGE

PLATES AND KNIVES FOR MINCERS

UNGER

PLATES

Hole diameter mm	R70	H82	A90	B98	D114	E130	GU160
2 - 2,5	—	—	—	—	—	—	—
3 - 3,5 - 4	—	—	—	—	—	—	—
4,5 - 5 - 6 - 8 - 10	—	—	—	—	—	—	—
13 - 18 - 20	—	—	—	—	—	—	—

KNIFE PLATES

Precut 00 (inclined holes)	—	—	—	—	—	—	—
Precut 00 (straight holes)	—	—	—	—	—	—	—

STANDARD KNIVES

Knife with removable blades *	—	—	—	—	—	—	—
Box of 9 blades	—	—	—	—	—	—	—
Packet of 5 screws	—	—	—	—	—	—	—
Key	—	—	—	—	—	—	—

*Mounted on all professional mincers: refrigerated mincers, DRC 82 and DRC 98.

LICOSWISS® KNIVES

3 and 4-branch monobloc knives *	—	—	—	—	—	—	—
----------------------------------	---	---	---	---	---	---	---

*Mounted on all industrial mincers: DRC 98S, DRC 114ST, DRC 114, DRC 130 and automatic mixing mincers.

Knife with removable blades	—	—	—	—	—	—	—
Box of 9 blades	—	—	—	—	—	—	—
Packet of 5 screws	—	—	—	—	—	—	—
Key	—	—	—	—	—	—	—

ENTERPRISE

PLATES

Hole diameter mm	N5	N8	N12	N22	N32	N42
2	—	—	—	—	—	—
2,5 - 3	—	—	—	—	—	—
3,5	—	—	—	—	—	—
4-4,5-5-6-8-10-13-18*-20*	—	—	—	—	—	—

*18-20 except N5/N8

STANDARD KNIVES

Knife 4 branches *	—	—	—	—	—	—
--------------------	---	---	---	---	---	---

*Mounted on all professional mincers: Refrigerated mincers, DRC 22L, DRC 22 and DRC 32.


NINJA KNIVES

Knife 3 branches	—	—	—	—	—	—
------------------	---	---	---	---	---	---

LICOSWISS® KNIVES


Monobloc knives 4 branches *	—	—	—	—	—	—
------------------------------	---	---	---	---	---	---

*Mounted on all industrial mincers: DRC 32S, DRC 42 and automatic mixer mincers.





BAND SAW BLADES



Model	Size (mm)	Model	Size (mm)	Model	Size (mm)
SS1550	1550 x 16	SS1800	1800 x 16	SS2340	2340 x 16
SS1590	1590 x 16	SS1820	1820 x 16	SS2400	2400 x 16
SS1600	1600 x 16	SS1830	1830 x 16	SS2430	2430 x 16
SS1620	1620 x 16	SS1840	1840 x 16	SS2440	2440 x 16
SS1640	1640 x 16	SS1860	1860 x 16	SS2490	2490 x 16
SS1650	1650 x 16	SS1980	1980 x 16	SS2500	2500 x 16
SS1705	1705 x 16	SS1985	1985 x 16	SS2845	2845 x 16
SS1740	1740 x 16	SS2040	2040 x 16	SS3150	3150 x 16
SS1750	1750 x 16	SS2170	2170 x 16	SS3155	3155 x 16
SS1760	1760 x 16	SS2311	2311 x 16	SS3370	3370 x 16

- Sold and packaged exclusively in boxes of 5 pieces
- 4 teeth per inch (4TPI), high-quality steel, hardened teeth
- Width 19 mm: Please contact us!



AMERICAN HANDSAW BLADES

Model	Size (mm)
17,5"	450
20"	500
25"	630



HANDSAW AMERICAN

Model	Size (mm)
17,5"	450
20"	500
25"	630



Our recognized expertise

Our ranges combine robustness, meticulous finishing, and thoughtful design. The footprint is minimal, and the use of stainless steel allows us to offer longevity and ease of cleaning.

Continuous inspections are carried out throughout our manufacturing process.

Our level of demand and quality of service have allowed us to build our reputation and be recognized for our extremely robust manufacturing. It is through our constant investments, both in human resources and in production capabilities, that we are now able to maintain this quality at the best price.



www.psv-groupe.com



Manufacturer

Usine du Berre au Loup D147 BP 20
95420 Genainville - France

Phone : +33 (0)1 34 46 86 86
info@psv-groupe.com